

METHOD AND APPARATUS FOR MANUFACTURING, FILLING
AND PACKAGING MEDICAL DEVICES AND MEDICAL CONTAINERS

Cross-Reference to Related Application

Sub B¹ This application claims the benefit under 35 U.S.C.
§ 119(e) of U.S. provisional application Serial No.
60/077,897 filed March 13, 1998 and U.S. provisional
5 application Serial No. 60/102,338 filed September 29,
1998, which are hereby incorporated by reference in their
entirety.

Field of the Invention

10 The present invention relates generally to a method
of manufacturing drug delivery and drug container
devices, such as syringe components, and packaging the
components in a clean, substantially particulate-free
area. More particularly, the invention is directed to a
15 method for manufacturing glass or plastic syringe barrels
and assembling and packaging the syringe barrels in a
clean room or locally controlled environment which is
clean and substantially free of airborne particulates.

Background of the Invention

20 Drug delivery devices are generally prepared by
molding or shaping the various components and then
assembling the components. The assembling steps and

FO2040" 60E26860

other processing operations typically produce a device that subsequently must be cleaned to remove particulates adhering to the surfaces to satisfy cleanliness standards for drug delivery devices. After cleaning, the drug
5 delivery devices are packaged and sterilized.

Syringes have been classified into several general types. The first type is assembled and placed in sterile packaging which can be shipped with a vial or ampoule of a drug or other injectable solution. The vial or ampoule
10 is generally made of glass or other clear material that does not interfere with the stability of the drug during prolonged storage. The syringe is filled with the drug or other solution at the point of use and injected into the patient. Another type of syringe is packaged with a
15 vial filled with a powdered or lyophilized drug which is dissolved in water or other suitable solvent prior to charging into the syringe.

These syringes have the disadvantage of increasing the time and difficulty of filling the syringe at the
20 point of use with increased possibility of contamination of the syringe and/or drug solution. There is a further risk of glass particles from the ampoules contaminating the drug solution when the ampoules are opened.

Several of these disadvantages are overcome by
25 providing prefilled syringes which can be filled with a suitable drug solution prior to use. Prefilled syringes, as the term is known in the art, are syringes that are filled by the drug manufacturer and shipped to the health care provider ready for use. Prefilled syringes have the

09897309-070201
102020-68650

advantage of convenience and ease of application with reduced risk of contamination of the drug solution. A difficulty in producing prefilled syringes, if they are made of plastic rather than glass, is selecting suitable materials that maintain their clarity for extended periods of time and do not contaminate or react with the drug solution.

Syringes and other drug delivery devices are generally assembled and packaged in clean rooms to maintain proper cleanliness levels. The clean rooms are equipped with extensive filter assemblies and air control systems to remove particulates and pyrogens from the air in the room and to prevent particulates and pyrogens from entering the room. The operators and other personnel in the clean room are required to wear appropriate protective garments to reduce contamination of the air and the drug delivery devices being manufactured or assembled. As people and equipment enter and leave the clean room, the risk of contamination and introduction of foreign particulates and pyrogens increases.

Various operations are able to form clean and sterile drug delivery devices. However, subsequent handling, filling and printing of the drug delivery device can contaminate the device. It is then necessary to clean and sterilize the drug delivery device before use.

Accordingly, there is a continuing need in the industry for an improved system for manufacturing and

09897309-070201

assembling clean and sterile medical devices and filling such devices.

Summary of the Invention

5 The present invention is directed to a method and apparatus for maintaining a clean environment during the manufacture and assembly of medical devices such as drug delivery devices and medical container devices. More specifically, the invention is directed to the manufacture of various medical containers, drug delivery and drug container devices which are clean and have a low bio-burden or are sterile at the completion of the manufacturing step and immediately transferring the devices to a clean room or to a locally controlled environment to maintain cleanliness levels while assembling and packaging the devices. The medical devices can be filled with a suitable substance such as, saline solutions, flush solutions or contrast agents, pharmaceutical agents and vaccines, in either a dry or liquid state.

10 20 Accordingly, a primary object of the invention is to manufacture medical container devices immediately upstream of at least one housing assembly which defines a locally controlled environment. The medical containers are manufactured from glass or plastic under conditions which produce a substantially clean and sterile part. The housing assembly receives the medical containers directly from the manufacturing apparatus without a prior cleaning step so that the containers can be assembled

09897309-070201
T02020-60E26860

within the housing assembly under controlled conditions to maintain predetermined cleanliness standards for medical containers and devices.

Another object of the invention is to provide a
5 method for manufacturing a substantially clean and low
bio-burden medical containers, such as a syringe barrel
and assembling the syringe barrel with various
components, such as a tip closure or Luer lock, in a
locally controlled environment without the need for a
10 water washing step.

A further object of the invention is to provide a
method and apparatus for forming glass medical
containers, such as drug delivery devices or components,
annealing the glass medical containers, and then
15 immediately capturing the annealed container in an
environmentally controlled area to maintain a
predetermined cleanliness and low bio-burden. The
annealed glass medical containers are captured from the
annealing oven in a manner to maintain the cleanliness
20 and low bio-burden to avoid a mandatory cleaning step.
The environmentally controlled area can be a clean room
or a locally controlled environment.

Another object of the invention is to provide a
method and apparatus for producing clean medical
25 containers and delivering the devices to a housing
assembly which defines a locally controlled environment,
where the housing assembly includes a HEPA filter and a
fan or blower to feed filtered air into the housing and

09897309-070201
T02070-60E26860

maintain the housing assembly at predetermined cleanliness levels.

In embodiments of the invention, the medical containers are glass syringe barrels, and particularly prefillable glass syringe barrels, manufactured by processes which produce substantially clean and low bio-burden or sterile syringe barrels. The glass syringe barrels are made from cylindrical glass tubes that are cut to a desired length. The tubes are then fed to a forming machine which in one embodiment heats the ends of the tubes and forms a flange at one end and a tip at the opposite end. The glass syringe barrels are annealed by heating in a Lehr or annealing oven to at least about 560°C for an appropriate time to relieve stresses in the glass. The annealing produces a clean and low bio-burden syringe barrel which is then immediately transferred to an environmentally controlled area substantially without contamination.

A further object of the invention is to provide a housing assembly which maintains a locally controlled environment for assembling medical containers and packaging an array of medical containers in closed second containers. The medical containers can be sterilized in a subsequent step.

The housing assembly defining the locally controlled environment can be a portable unit having a work surface for performing the desired operations manually or automatically. The work surface is enclosed by side panels, at least some of which are preferably transparent

09897309-010201

to allow viewing and inspection by an operator located outside the housing. The assembly includes a top wall coupled to the side panels to define an enclosure. The assembly includes a fan or blower assembly and a filter
5 assembly to direct filtered air into the housing and maintain a clean environment and can be operated to maintain a positive pressure in the housing assembly to prevent the infiltration of unfiltered air. An optional exhaust fan can also be provided to draw air downwardly
10 through the housing assembly and exhaust the air without causing a negative pressure in the housing assembly.

In one embodiment of the invention, the medical containers exit the forming device and are immediately captured in an environmentally controlled area to
15 maintain cleanliness. The medical devices, such as syringe barrels, in the housing assembly optionally can be cleaned by streams of clean filtered air or ionized air when necessary. The cleaning air removes substantially all particulates that may be adhered to the
20 inner and outer surfaces of the barrel to attain the desired cleanliness level. A vacuum exhaust can be provided in the area of the barrel to carry the particulates away from the barrel and out of the housing assembly. Tip closures, Luer locks or syringe needles
25 with their associated needle sheaths are also supplied to the housing assembly where they can be cleaned with filtered air or ionized air. The tip closures, Luer locks and needles are coupled to the syringe barrels. A lubricant is preferably applied to the inner surface of

102020" 60E26860

the syringe barrel, and the syringe barrels are placed in a grid or tray which is in turn placed in a container such as a tub. A plastic sheet is placed over the tray and the tub is closed with a sheet of flexible material which generally is heat-sealed to the tub. The tub is then enclosed in an outer wrap such as a plastic bag which is heat sealed. The tub, outer wrap and contents are sterilized by a sterilizing gas or radiation. Some or all of these operations can be conducted in a single housing assembly or in a plurality of housing assemblies coupled together.

A method of producing prefillable, glass syringe barrels in accordance with the present invention comprises the steps of supplying a glass tube to a forming device and forming a hollow syringe barrel having a flange at one end and a tip at the other end. The syringe barrels are annealed in a Lehr oven, cooled, and received in a first housing assembly having an air filtering device to maintain a predetermined cleanliness level therein, and a plurality of tip closures are supplied to the first housing assembly and are assembled with the syringe barrels. A stream of filtered air is directed to the syringe barrels and syringe components to remove particulates therefrom and clean the outer surfaces thereof. The assembled syringe barrels and syringe components are conveyed to a second housing assembly having a filtering device for maintaining a predetermined cleanliness level, and a lubricant is preferably applied to the inner surfaces of the syringe

09897309-070201

barrels. In a third housing assembly, the syringe barrels are formed into an array and placed into a container having a closed bottom, side walls and an open top. Thereafter, the container is conveyed to a fourth housing assembly having an air filtering device to maintain a predetermined cleanliness level, and a closure is applied to the container to seal the container.

The aspects of the invention are further attained by providing a method of producing a filled syringe comprising the steps of forming a plastic syringe barrel in an injection molding machine where the syringe barrel has a cylindrical side wall, an open proximal receiving end and a frustoconically shaped outlet nozzle at its distal end, and transferring the syringe barrel, without any additional cleaning or sterilization, into an environmentally controlled area to maintain a predetermined cleanliness level. A stream of filtered air is directed toward the syringe barrel in the environmentally controlled area to remove particles from surfaces thereof to clean the syringe barrel. A tip cap is delivered to the environmentally controlled area and the tip cap is assembled onto the outlet nozzle of the syringe barrel to close the outlet nozzle and the syringe barrel is filled with a substance through its open proximal end. A stopper is delivered to the environmentally controlled area and is inserted into the open proximal end of the barrel to form a prefilled syringe. The prefilled syringe is then removed from the environmentally controlled area. In further embodiments,

09897309-07004
FO2020-60E26860

a stopper is applied to the syringe followed by filling the syringe through the tip or nozzle and then closing with a tip cap.

These and other aspects, advantages and salient features of the invention will become apparent to one skilled in the art from the annexed drawings and the following detailed description which discloses preferred embodiments of the invention.

Brief Description of the Drawings

Referring to the drawings which form a part of this original disclosure:

Figure 1 is an exploded side elevational view of a glass syringe showing the Luer locking collar;

Figure 2 is an end view of the Luer locking collar of Figure 1;

Figure 3 is a side elevational view of an assembled syringe barrel in an embodiment of the invention;

Figure 4 is a side elevational view of a plastic syringe in a further embodiment;

Figure 5 is an exploded perspective view of a syringe barrel tub enclosure in an embodiment of the invention;

Figure 6 is a flow chart of the manufacturing steps for forming glass syringe barrels;

Figure 7 is a top view of housing assemblies defining a locally controlled environment for cleaning, assembling and packaging syringe barrels in accordance with one embodiment of the invention;

09897309-070201

Figure 8 is a perspective view of the locally controlled environment of Figure 7;

Figure 9 is a flow chart of the assembly steps for packaging the syringe barrel assemblies;

5 Figure 10 is a flow chart of the filling steps for filling syringe barrels to produce prefilled syringes; and

10 Figure 11 is a side elevational view of a glass forming and glass annealing apparatus coupled to a clean room for assembling and packaging the syringe barrels in accordance with another embodiment of the invention.

Detailed Description of the Preferred Embodiments

15 The present invention is directed to a method and apparatus for manufacturing and thereafter assembling and packaging medical containers, drug delivery devices and drug containers, such as vials, syringe barrels and prefilled syringes, in a clean, environmentally controlled area. As used herein, medical containers for containing and/or dispensing substances include vials and
20 injection devices such as syringes. In addition, as used herein, a substance includes, for example, water, saline solutions, flush solutions and contrasting agents, pharmaceutical agents and vaccines in either a dry state or liquid state. The medical containers can be syringe
25 barrels formed from a base material such as glass or plastic. The syringe barrels are used to assemble a syringe 10 as shown in Figure 1. Although embodiments of the invention are disclosed as a hypodermic syringe

09897309"0"0201
FO2020"60E26860

assembly, it is within the purview of the present invention to include various other drug containers, such as plastic or glass cylindrical reservoirs having resilient stoppers and/or closures at one or both ends, or other drug delivery devices or appliances which require a clean environment during manufacture or assembly.

Referring to Figures 1 and 2, the medical container is a syringe 10 including a glass syringe barrel 12, a plastic plunger rod and attached rubber stopper or piston (not shown) and a tip closure 15 or needle sheath closure 16. In further embodiments, the syringe can be a needleless syringe as known in the art. Syringe barrel 12 in the embodiment illustrated has a cylindrical side wall 18, a flange 20 at a receiving end 22, and a frustoconical outlet nozzle 24 at a discharge end of a barrel tip 26. A Luer locking collar 28 encircles the outlet nozzle 24 to define an annular space 30 surrounding the outlet nozzle 24. Side wall 18 can include suitable printed indicia for indicating the volume of the syringe, the name of the manufacturer and the like.

Luer locking collar 28 is generally a plastic collar that is able to be snapped onto the nozzle 24 of the syringe barrel tip 26. As shown in Figures 1 and 2, Luer locking collar 28 includes an annular sleeve 30 having an inner wall 32 with internal threads 34. The annular sleeve 30 has an open end 36 for coupling with an externally threaded member. The sleeve 30 further has a

09897309 070201
FOI 2020-05076860

5

10

15

20

25

heat sealing, threaded closures and the like. In further embodiments, the syringe barrel is a cylindrical tube having plastic components attached to each end forming a thumb flange and a nozzle, respectively.

5 A plunger rod and a stopper or piston can be provided for assembling with the syringe barrel to manufacture prefilled syringe barrels. The stopper is typically made of a molded flexible material, such as rubber, that is sufficiently pliable and flexible to
10 readily conform to the inner surface of the syringe barrel and form a fluid tight seal. The plunger rod is typically made of plastic.

Tip closure 15 is dimensioned to close the frustoconical nozzle 24 of syringe barrel 12. Referring
15 to Figure 1, tip closure 15 has a slight frustoconical sleeve 49 with a closed end 50 and an outer annular flange 52. Sleeve 49 is dimensioned to fit securely over frustoconical nozzle 24. Tip closure 15 is typically made from flexible rubber-like materials, rigid materials
20 or peelable strip materials as known in the art.

Referring to Figure 3, a further embodiment includes a glass syringe barrel 13 having a tapered outlet nozzle tip 17 with an enlarged end 19, a side wall 21 and a flange 23. A protective plastic needle sheath 16 has an
25 open end 64 for coupling with syringe tip 17 and a closed end 66 opposite open end 64. Protective sheath 16 has a hollow, substantially cylindrical shape and can be dimensioned to receive a needle 60. In the embodiment illustrated, sheath 16 contacts and closes off the tip of

TOP SECRET

needle 60 to prevent fluid leakage. In further
embodiments, the side walls 68 are spaced from needle 60
so that sheath 62 does not contact needle 60. The needle
60 can be a stainless steel needle secured in the tip 17
5 by a suitable adhesive as known in the art.

Figure 4 illustrates an embodiment where the medical
container is a syringe 10' including a plastic syringe
barrel 12', a plastic plunger 14' and a plastic tip
closure 15'. In further embodiments, syringe 10' can be
10 a needleless syringe or include a needle tip closure as
known in the art. Syringe barrel 12' has a cylindrical
sidewall 18', a flange 20' at a receiving end 22', and a
frustoconical outlet nozzle 24' at a discharge end 26'.
Collar 28' encircles the outlet nozzle 24' to define an
15 annular space 30' surrounding the outlet nozzle 24'. An
inner surface of collar 28' includes a threaded portion
32'. Sidewall 18' can include suitable printed indicia
for indicating the volume of the syringe, the name of the
manufacturer and the like.

20 Plunger 14' includes a molded flexible stopper 34'
having a frustoconical end face 35', and a plurality of
annular ridges 36' dimensioned to form fluid tight
contact with the inner surface 19' of sidewall 18' of
syringe barrel 12'. A plunger rod 37' includes in
25 threaded member 38' which is coupled to an internally
threaded recess 40' in stopper 34'. Plunger rod 36' has
four vanes 42' extending outwardly from a center
longitudinal axis and extending at substantially right

FO2020-0602660

Referring to Figure 5, a plurality of syringe barrel assemblies 12 are placed in a container or tub package

5 82. In the embodiment illustrated, the syringe
assemblies include a syringe barrel 12, a Luer locking
collar 28 and a tip cap 15. In further embodiments, the
syringe barrel assemblies can include a needle cannula
and sheath as shown in Figure 3. The syringe barrel
10 assemblies can be placed in any suitable package or
container depending on the particular syringe and its end
use. A tray 84 is provided having a plurality of spaced-
apart openings 86 and collars 88 extending upward for
supporting the syringe barrels 12. In the embodiment
15 illustrated, openings 86 and collars 88 are arranged in a
series of rows and columns and are uniformly spaced
apart. Tray 84 includes cut-out portions 90 for lifting
and easily gripping the tray 84 and to orient the tray
during various processing and filling operations. Tray
20 84 is nested in a suitable container such as a tub 92.
Tub 92 includes side walls 94 and a bottom wall 96. A
stepped portion 98 of tub 92 is formed in side walls 96
to support tray 84 so that the ends of syringe barrels 12
can be spaced from bottom wall 96. In other embodiments,
25 the ends of syringe barrels can contact bottom wall 96.
A peripheral flange 100 extends outward from the open top
end of side walls 94. Tub 92 is typically an integrally
formed rigid plastic unit made by a suitable molding

process, such as injection molding, vacuum forming or blow molding.

Tray 84 supports an array of syringe barrels 12 and is positioned in tub 92. A protective layer of sheet material 102, such as polyethylene, foam or other plastic, is positioned to cover tray 84 and the syringe barrels 12. Preferably, sheet 102 is substantially the same size as tray 84. A closure or cover sheet 104 is then positioned on peripheral flange 100 and is sealed on the flange to completely enclose the array of syringe barrels 12. The tub 92 is then enclosed in a sealed plastic bag or wrapper. Typically, the cover sheet 104 is a thermoplastic material that is heat-sealed to flange 100 to form a complete seal. A suitable cover sheet 104 is a gas-permeable material such as a spun bonded polyolefin sold under the trademark TYVEK by E.I. DuPont & Co. This allows the syringe barrels 12 to be gas sterilized, if desired, while they are in the sealed tub 92. In further embodiments, the syringe barrels can be sterilized by radiation.

The syringe of Figures 1-4 can be assembled by the manufacturer and packaged in suitable clean and sterile packaging. The syringes may be packaged individually or in bulk. One example of bulk packaging places a plurality of the syringe barrels laying flat in a molded tray. A plurality of the trays are stacked in a carton which is then closed and sterilized. In embodiments of the invention, the syringe components are partially assembled so that prefilled syringes can be produced by

10202070-60E/6860

5 assembling the barrels and tip closures of the syringes.

Syringe barrels 12 in embodiments of the invention are made of glass. The glass syringe barrels are formed and annealed and then captured in a clean, locally
20 controlled environment or clean room immediately upon being ejected or discharged from the annealing oven to maintain the syringe barrels in a substantially clean condition having low bio-burden. Glass and molded plastic drug containers and syringe barrels are typically
25 molded at sufficient temperatures and conditions to produce clean and low bio-burden devices. The clean and low bio-burden syringe barrels are captured in an enclosed housing assembly to maintain cleanliness and low

bio-burden without exposing to unfiltered air and contaminants.

The glass syringe barrels are manufactured by the steps as shown in the flow chart of Figure 6 using standard glass forming techniques and equipment. Referring to Figure 6, a glass tube or "cane" having a working length and a diameter corresponding to the diameter of the finished syringe barrel is provided from a supply indicated in block 220. The glass tubes can be heated in a Lehr oven of at least about 560°C for an appropriate length of time to anneal the glass, although annealing is generally not necessary at this stage. The glass tubes are then cut to a working length as indicated in block 222 and are fed to a syringe barrel forming device. The syringe barrel forming device heats the ends of the glass tube to a softening temperature and forms a thumb flange at the proximal end and an outlet nozzle tip at the distal end as indicated in block 224. The temperature of the glass during the tip and flange formation is generally about 760°-1100°C. The formed glass syringe barrels are then heated in a Lehr oven to at least about 560°C for an appropriate length of time to anneal the glass and relieve stresses in the syringe barrel as indicated in block 226. The length of time for the annealing is dependent on the particular glass being used and the annealing temperature as known by those skilled in the art. Thereafter, the syringe barrels are cooled and immediately transferred to a clean environment for maintaining a clean and low bio-burden condition as

09897309-070201

5 It has been found that glass syringe barrels exiting
a Lehr oven at about 590°C have satisfactorily low
particulate levels on their surfaces to meet drug
delivery device cleanliness standards. Test results have
shown that barrels after heating at 590°C for about 30
0 minutes have an average of 8.55 particles per barrel with
a particle size of about 5-24 microns, with the barrels
being substantially free of particles having a particle
size of 25 microns or larger. Tests have also
demonstrated that the syringe barrels have satisfactory
sterility, toxicity and pyrogenicity levels as determined
5 by standard testing procedures for drug delivery devices.

In an embodiment of the invention, the syringe barrels and the barrel assembly tub package 84 are produced using an apparatus 108 depicted in Figures 7 and 8 by the method outlined in the flow charts of Figures 6 and 9. The apparatus 108 in the embodiment shown includes several modular housing assemblies 112, 114, 116 and 118 which are coupled together. Preferably, the housing assemblies are modular and portable so that they

5

10

15

20

25

In one embodiment of the invention, the HEPA filters are selected to maintain the housing assemblies and the respective work spaces therein at levels meeting or exceeding Class 100 conditions with respect to

5 particulates as defined by Federal Standard No. 209E, "Airborne Particulate Cleanliness Classes in Clean Rooms and Clean Zones", approved by the General Services Administration (September 11, 1992). In other

embodiments, the HEPA filters are selected to maintain

10 cleanliness standards as needed which can be higher or lower than Class 100.

Air blower 126 directs clean filtered air downward through the housing assembly to an outlet (not shown) in the lower end of the housing assembly. An optional

15 exhaust fan 127 can be included to draw air and any particulates or other contaminants out of the housing assembly. One or more of the side walls 120 can include an optional access opening 129 as shown in enclosure 116 to enable an operator to reach into the workspace and

20 perform various operations. As shown in Figure 7, a chair 131 or stool is provided for the operator. A positive pressure is preferably maintained in the workspace 122 to prevent air from entering through the access opening 129.

25 In the embodiment illustrated, the glass syringe barrels are formed in the glass forming apparatus 161 from glass cylinders. The formed glass syringe barrels are transferred to a Lehr oven 162 where the barrels are heated to at least 560°C to anneal the glass and to

09897309.070201
FO2040 60E76860

5

10

25

enclosure 141 as needed to maintain desired cleanliness levels.

Referring to Figure 7, housing assembly 112 encloses an apparatus 133 for assembling the syringe barrels 12 with the selected component, such as a tip closure, needle cannula, Luer lock collar and needle sheath. The syringe barrels 12, which can be printed or unprinted, are essentially clean when fed directly from the Lehr oven 162. The syringe barrels are fed from the Lehr oven 162 or other supply to a recess 132 in a rotating table 134. Table 134 rotates to station 135 where clean components are fed from a supply entrance 136 and coupled to the ends of the syringe barrels 12 to produce a syringe barrel assembly 137 as shown in Figure 1. The table 134 continues to rotate to station 138 where the syringe barrel assembly 137 is ejected onto a conveyor rail 140. Conveyor rail 140 is enclosed in a tunnel 141 to maintain the same cleanliness levels as in housing assembly 112. Preferably, the syringe barrel assemblies 137 are substantially clean and have a sufficiently low bio-burden so that further washing or cleaning steps can be eliminated. In embodiments where further cleaning is necessary, however, syringe barrel assemblies 137 are conveyed past nozzles 142 which direct streams of filtered, ionized air across the conveyor rail 140 to remove any particulates from the outer surfaces of syringe barrel assemblies 137 and to reduce static charge. Conveyor rail 140 has a discharge end 144 in housing assembly 114.

09897309-070201

09897309-070201
T02070-6026860

Housing assembly 114 contains a rotating table 146 having recesses 148 for receiving syringe barrel assemblies 137 from the conveyor rail 140. Table 146 rotates to carry the syringe barrel assemblies 137 to a cleaning station 150 where streams of filtered, ionized air are directed into the syringe barrel assemblies 137 to loosen and remove any particulates from their inner surfaces while a vacuum is applied to the inner surface to carry the particulates away. In preferred embodiments, the manufacturing process produces sufficiently clean syringe barrels so that this cleaning step is optional. Thereafter, table 146 rotates to carry the syringe barrel assemblies 137 to a lubricating station 152 where a thin coating of a lubricant is applied to the inner surface of the syringe barrel assemblies 137. The lubricant is preferably a silicone oil as known in the art. Table 146 then rotates to carry the syringe barrel assemblies 137 to a discharge station 154, where the syringe barrel assemblies 137 are discharged onto a conveyor rail 156 and conveyed to housing assembly 116.

In the embodiment illustrated, housing assembly 116 includes an access opening 129 in side wall 120 to enable an operator sitting on a seat or chair 131 to reach into the housing assembly 116. The opening 129 is dimensioned to enable the operator to perform various manual operations while maintaining the workstation area at the desired cleanliness level. In the embodiment illustrated, the operator examines the syringe barrel

assemblies 137 and places the assemblies in the tray 84 which is in the tub 92. The operator then places the protective sheet material 102 over the syringe barrel assemblies 137. The closure sheet 104 is then placed
5 over the tub 92 and the tub is manually placed in housing assembly 118 through an opening 158 in side wall 120. In further embodiments, the syringe barrel assemblies 137 are placed in tub 92 automatically by suitable machinery.

Within housing assembly 118 is a heated platen 160
10 for heat sealing the closure sheet 104 onto tub 92. The platen 160 is lowered onto the sheet 104 and the sheet is sealed to the flange 100 of the tub 92 to enclose the syringe barrel assemblies 137. Since the syringe barrel assemblies 137 are now enclosed in protective packaging,
15 the tub can be removed from the housing assembly 118 without the risk of contamination of the syringe barrel assemblies 137. The tub can then be sealed in a plastic bag or other protective outer wrap and placed in suitable shipping cartons. Standard heat sealing and bagging
20 devices are typically used.

Alternatively, the tub package 82 can be transferred from the housing assembly 118 to a further housing assembly 121 serving as a sterilization chamber. Sterilization can be, for example, by gamma or beta
25 radiation, hot air or steam autoclave. In preferred embodiments, the cover sheet 104 is a gas permeable material which is permeable to ethylene oxide sterilizing gas. Typically, the tub package 82 is exposed to ethylene oxide for sufficient time to permeate the

09897309-070201
1022010-6026880

closure sheet and sterilize the contents thereof. The chamber is then evacuated and purged with carbon dioxide or other gas to remove the ethylene oxide. The plastic bagging operation described above may then be performed.

5 In the embodiment illustrated in Figure 7, sterilization chamber 121 is connected in line with housing assembly 118 to receive the tub package 82. Alternatively, the tub packages 82 are transferred to a sterilization chamber at a different location.

10 Sterilization can also be performed after placing the packages 82 in suitable shipping cartons.

The apparatus of Figure 7 is intended to be exemplary of one embodiment of the invention. In this embodiment, the housing assemblies define different work
15 stations and are in modular form for assembly and disassembly. In further embodiments, apparatus 108 can be a single housing enclosing all of the work stations.

Referring to Figure 9, a flow chart depicts the method of assembly of the tub package 82. Clean syringe
20 barrels are fed from a supply as indicated in block 170, and clean tip closures are fed from a supply as indicated in block 172. The syringe barrels can be fed to an optional print station as indicated in block 177. Optional needle cannulas as indicated in block 171,
25 needle shields as indicated in block 173 and Luer lock collars as indicated in block 175 are also fed from a supply. The syringe barrels and syringe components are supplied to a locally controlled environment for assembly of the components to the syringe barrels indicated in

09897309-070201

block 174. The syringe barrel and tip closure assemblies are conveyed through an optional stream of clean, ionized air to remove particulates from the outer surface of the syringe barrel assemblies as indicated in block 176. The
5 syringe barrel assemblies are then passed to a station where the inner surfaces of the syringe barrels are cleaned with filtered, ionized air and vacuum as indicated in block 178, and to a lubricating station where a lubricant is applied to the inner surfaces as
10 indicated in block 180.

The lubricated syringe assemblies are placed in the tray and tub as indicated in block 182, followed by the addition of a protective sheet as indicated in block 184 and an outer cover sheet as indicated in block 186. The
15 tub package is then placed in a heat sealer to seal the cover sheet to the tub as indicated in block 188. The sealed tub is enclosed in a plastic bag as indicated in block 190, followed by sterilization as indicated in block 192.

20 In a further embodiment, a housing assembly substantially as described above encloses a container filling device for filling the medical container with the desired substance. The container can be a suitable medical container such as a vial or syringe barrel. The
25 housing assembly includes an inlet for receiving the container and an air or water wash device as needed for cleaning the container. The filling device fills the clean containers and attaches a suitable closure to close the container. The cleaning, filling and assembling

09897309-070201

devices can be enclosed in a single housing assembly or enclosed in separate housing assemblies connected together in series by chutes, tunnels or other enclosures. The drug containers can be molded plastic or
5 formed glass which are captured immediately after molding or forming in the housing assembly to maintain the clean and low bio-burden levels. The molding and forming devices can be positioned next to the housing assembly and connected thereto by a closed conveyor, tunnel or
10 chute. In further embodiments, the molding or forming device can be enclosed in a housing assembly to define an environmentally controlled area to maintain cleanliness standards.

The package 82 of syringe barrel assemblies and the
15 packaged stoppers can be transferred to an enclosed housing assembly for filling the syringe barrel and assembling a prefilled syringe. Each syringe barrel is filled with a predetermined amount of a substance while held in a closed, clean containment area. The
20 containment area is then evacuated and the plunger and stopper assembly is positioned in the open end of the syringe barrel. The vacuum is then released and the plunger is drawn into the syringe barrel by the vacuum remaining within the barrel. Alternatively, the plunger
25 and syringe barrel can be assembled by a vent tube stoppering process as known in the art. Thereafter, the assembled syringes are packaged as prefilled syringes and sold for use by health care providers.

FOUO 2010-06-04

Figure 10 illustrates a flow chart for a method of producing a prefilled syringe. Referring to Figure 10, a supply of preformed syringe barrels are formed in a syringe barrel molding machine indicated by block 220.

- 5 The molded syringe barrels are transferred into a locally controlled environment indicated by 222 preferably without any additional cleaning or sterilizing steps. It is preferred that the transferring of molded syringe barrels to the locally controlled environment be
- 10 immediate. The syringe barrels are washed with air to remove particulates and coated with a lubricant such as silicone lubricating oil on the inner surface as indicated by block 224. A supply of tip caps indicated by block 226 is fed into the locally controlled
- 15 environment 222. The tip caps are air washed as indicated by block 228. The cleaned tip caps and syringe barrels are conveyed to an assembly device indicated by block 230 where the tip caps are assembled onto the syringe barrel to close the tip or nozzle of the syringe
- 20 barrel. The syringe barrel assemblies are then conveyed to a filing station indicate by block 232 where the syringe barrel is filled with a substance as defined herein.

- A supply of stoppers indicated by block 234 is
- 25 transferred to a washing station indicated by block 236 where a silicone lubricant is applied to the stoppers. The lubricated stoppers are then delivered to a transfer feed device indicated by block 240 within the locally controlled environment 222. The stoppers are then

09897309-070201
T02020-60E46860

assembled with the filled syringe barrels indicated by
block 242 to close the syringe. In particular, the
stopper is inserted into the open proximal receiving end
of the syringe barrel. The prefilled syringes are
5 preferably inspected for defects as indicated by block
244 and discharged from the locally controlled
environment 222, sterilized as indicated by block 246 and
packaged either individually or in bulk for transporting
indicated by block 248. Suitable sterilization methods
10 include heat, steam, radiation and gas sterilization as
known in the art. In some uses, for example, if the
syringe is to be used in a surgical procedure, the
sterilization step should occur after the syringe is
packaged. It is also within the purview of the present
15 invention to include sterilization of the syringe both
before and after packaging.

In the method of Figure 10, the syringe barrels are
breach filled and the tip cap is coupled to the barrel
before filling. It will be understood by those skilled
20 in the art that a stopper and/or syringe plunger can be
coupled to the syringe barrel before filling and the
syringe barrel filled through the tip or nozzle.
Thereafter, a tip cap or needle can be attached to the
filled syringe barrel to close the tip. Accordingly,
25 medical containers such as the syringe can be filled by
known filling methods. Exemplary methods for filling
syringes and other medical containers are disclosed in
U.S. Patent No. 5,620,425 to Hefferman et al., U.S.
Patent No. 5,597,530 to Smith et al., U.S. Patent No.

09897309-070201

5 al., which are hereby incorporated by reference in their
entirety.

10 filling syringe barrels to form prefilled syringes and to
produce prefilled drug containers. It will be
appreciated that other medical containers can be
assembled, constructed or packaged in the locally
controlled environment. Examples of containers which can
15 be packaged including various drug containers, vials,
ampoules or other containers where a clean environment is
required during the processing step. In addition, the
cleanliness standard for the locally controlled
environment is determined by the air filtration system to
20 obtain a sufficiently low particulate and pyrogen level
as required. In the embodiment disclosed, the HEPA
filters are sufficient to maintain a Class 100
cleanliness standard in each of the housing assemblies.
In further embodiments, the HEPA filters can be selected
25 to attain Class 10, Class 10,000 or Class 100,000
cleanliness conditions.

Figure 11 illustrates a second embodiment of the manufacturing and packing of medical appliances. The assembly is similar to the embodiment of Figure 8 except

that assembly and packaging apparatus 108' is contained in a clean room 250. In this embodiment, similar components are identified by the same reference number with the addition of a prime. Glass syringe barrels 12' are manufactured in a glass forming apparatus 160'. The syringe barrels 12' are conveyed by conveyor 164' to an annealing oven 162'. A closed tunnel 168' supporting a conveyor 170' delivers the syringe barrels 12' to a clean room 250. The clean room can be a standard clean room having suitable air blowers, HEPA filters, temperature and antistatic controls to maintain the cleanliness levels within prescribed limits determined by the selected class.

The glass syringe barrels are conveyed through an opening 252 in the clean room 250 and delivered to the assembly and packaging apparatus 108'. The syringe barrels can be further cleaned, assembled with syringe components and packaged in trays and tubs as in the previous embodiment. Optionally, the syringe barrels can be filled to produce prefilled syringes before packaging. The packaged syringe barrels 82' are then placed in cartons or other shipping containers for shipping to the ultimate consumer. It will be understood molded plastic drug containers can be molded and captured immediately after molding in a similar clean room where the drug containers can be filled and/or packaged.

Although certain embodiments have been selected to illustrate the invention, it will be apparent to one skilled in the art that other embodiments can be used

09897309 "0"0201

without departing from the scope of the invention. For
example, processes within the scope of the invention can
be used with either glass or plastic syringe barrels
through the changing of conditions to accommodate the
5 requirements of glass or plastic while still following
the process steps.

TO2040" 60E26860